



LEGEND

- Application Site
- Materials entering site for restoration and recovery/recycling
- Recovered materials to be used in quarry restoration
- Materials to be crushed into recycled aggregates and exported
- Empty lorries exiting site without the need to use the weighbridge

NOTES:

- ① Loads will be directed to SRF or to quarry void.
- ② Pure clay and non-recoverable/recyclable materials placed into void to assist with quarry restoration.
- ③ If suitable for SRF, load will be tipped and put through process of recovery/recycling.
- ④ Recovered materials placed in void to assist with quarry restoration.
- ⑤ Selected material capable of being recycled (i.e. bricks, concrete, tiles, ceramics) will be separated and crushed into recycled aggregates.
- ⑥ Crushed materials (6F5, Type 1) will be exported.
- ⑦ Exit for lorries which are not exporting material off-site/do not need to go via weighbridge.

Client

FRANKS

Project

Mercers South - Soils Recovery

Title

Indicative Layout - Soils Recovery and Aggregates Recycling (SRF)

Size	A3	Scale	1: 500	Date	14.06.22	Created by	CD	Reviewer	NR
Drawing No.	MS/SR/3							Rev	B

DRaW (UK) Ltd
Morwick Hall
York Road
Leeds
LS15 4TA
t: 0113 8232871
e: info@draw-ltd.com
www.draw-ltd.com

This page is intentionally left blank